



D24000S-QS

Slide Table Wet Tile Saw & Leg Stand 220V

FEATURES

- Stainless steel rail system is integrated into the tile saw frame, ensuring accurate cuts
- Cantilevering rail / cart system allows for 610 mm ripping capacity
- Low weight allows one person to transport and set up saw
- Plunge feature allows the user to make quick plunge cuts for electrical outlets together with an integrated 45 / 22.5 degree feature for quick angle cuts
- Dual water nozzles can be adjusted for optimal water placement on the blade in order to minimize over-spray and mist
- Rear and side water attachments can be placed on the tile saw to catch overspray - keeping the water in the pan
- Removable cutting cart for easy cleaning of tile saw
- Edge guide with two positions (90 & 45 degree) allows easy line up of corner cuts
- Integrated portable residual current device (PRCD) circuit breaker for increased user protection

SPECIFICATIONS

Power Input	1600 Watts
Wheel Diameter	250 mm
Bore Size	25.4 mm
No Load Speed	4200 rpm
Depth of cut	95 mm
Max. Crosscut Capacity at 90°	610 mm
Max. Crosscut Capacity at 45°	450 mm
Width	690 mm
Length	860 mm
Weight	32 kg
Hand/Arm Vibration	2.4 m/s ²
Uncertainty K 1 (Vibration)	1.5 m/s ²
Sound Pressure	90 dB(A)
Sound Pressure Uncertainty	3 dB(A)
Sound Power	103 dB(A)
Sound Power Uncertainty	3.1 dB(A)