

D25144K-B5

HD SDS Plus Combination Hammer
with QCC, 28mm, 220V



FEATURES

- Ideal for drilling in concrete and masonry from 4 to 28mm
- Rotation stop for light chiseling work in masonry, stone and concrete
- Tool free interchangeable tool holder and 13mm keyless
- Impact-stop for drilling in wood, steel, etc.
- Very high rate of penetration through optimally tuned electro-pneumatic hammer mill
- Safety clutch for active protection of user and machine
- Electronic speed and blow regulation
- Ergonomic rubberized grip areas
- Ergonomic rubberized auxiliary handle with light
- Very long service life due fully synchronized transmission
- Maximum dust protection through innovative sealing system
- Extremely compact and robust construction

SPECIFICATIONS

Bit retainer	SDS-Plus
Power Input	900
Power output	700
Impact energy (measured according to EPTA 05/2009)	3.0 J
No load speed	0-1450 rev/ min
Blows per Minute	0-5350 bpm
Max. Drilling capacity (Concrete)	28 mm
Max. Drilling capacity (Core Bit)	65 mm
Max. Drilling capacity (Wood)	30 mm
Max. Drilling capacity (Metal)	13 mm
Weight	3.1 kg
Length	360 mm
Height	210 mm
Width	75 mm

Vibrations - Drilling in concrete Hammer	14.9 m/s ²
Uncertainty K 1 (Vibration)	1.5 m/s ²
Hand / Arm Vibration - Chiselling	13.8 m/s ²
Uncertainty K 2 (Vibration)	1.5 m/s ²
Vibrations - Drilling in metal	<2.5 m/s ²
Uncertainty K 3 (Vibration)	1.5 m/s ²
Hand / arm vibration screws without knock function	<2.5 m/s ²
Uncertainty K 4 (vibration)	1.5 m/s ²
Sound pressure	89 dB (A)
Uncertainty K 1 (noise)	3.8 dB (A)
Sound pressure	100.1 dB (A)
Uncertainty K 2 (noise)	3.8 dB (A)