



D25731K-B5

48mm SDS Max Combination Hammer
7Kg 220V

FEATURES

- Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 48 mm in diameter. Core drilling up to 115 mm
- Active vibration control system incorporating a floating rear handle and damped side handle to reduce vibration
- Ergonomic, compact and slim line design maximizes control and offers easy access to confined spaces
- Electronic variable speed and impact energy control
- Lock-on switch for chipping
- Rotation-stop for demolition applications in brick, masonry and light chipping in concrete
- Brush wear and service indicators

SPECIFICATIONS

Tool Holder	SDS-Max
Power Input	1350 Watts
Power Output	840 Watt
Impact energy (EPTA 05/2009)	11 J
Load Speed	132-265 rpm
Blows per Minute	1225-2450 bpm
Max. Drilling Capacity [Concrete]	48 mm
Max. Drilling Capacity [Breakthrough bit]	80 mm
Max. Drilling Capacity [Core bit]	115 mm
Weight	8.7 kg
Length	528 mm
Height	268 mm
Width	116 mm
Hand/Arm Vibration - Hammer drilling into concrete	8.9 m/s ²
Uncertainty K 1 (Vibration)	1.5 m/s ²
Hand/Arm Vibration - Chiseling	8.1 m/s ²
Uncertainty K 2 (Vibration)	1.5 m/s ²
Sound Pressure	96 dB(A)
Sound Pressure Uncertainty	3 dB(A)
Sound Power	107 dB(A)
Sound Power Uncertainty	3 dB(A)