



D25831K-LX

5kg SDS Max Chipping Hammer w/ AVC
110V

FEATURES

- Ideal for light demolition, surface preparation or chiseling grooves and channel openings in brick, masonry and light concrete
- Active vibration control system incorporating a floating rear handle to reduce vibration
- Electronic variable speed and impact energy control
- Oil filled gearbox to ensure total component lubrication and superior heat dissipation
- Ergonomic, compact and slim line design maximizes control and offers easy access to confined spaces
- Variable chisel locking at 18 different positions to provide the perfect angles for any application
- Unique dust sealing protection to prevent even the finest dust ingress into the hammer mechanism delivering high durability and extended tool life
- Hammer mechanism is optimized by reducing the number of components and by improving dampening to deliver maximum impact energy and therefore the efficiency to break the hardest concrete
- Efficient mechanism delivers impact blows directly to the bit without losses through excessive vibration and rebound dampening reduces stress to the tool
- Soft rubber grip handles improve user comfort lowering fatigue during extended use
- Electronic service and brush wear indicator identifies when brushes need replacing and product should be serviced
- Excellent power to weight ratio: 8 Joules of impact energy delivered by a 6.1 kg hammer
- Magnesium housing for lower weight and excellent durability

SPECIFICATIONS

Tool Holder	SDS-Max
Power Input	1250 Watts
Power Output	615 Watt
Impact energy (EPTA 05/2009)	8 J
Blows per Minute	1430-2840 bpm
Weight	6.1 kg
Length	477 mm
Height	245 mm
Width	104 mm
Hand/Arm Vibration - Chiseling	8.3 m/s ²
Uncertainty K 2 (Vibration)	1.5 m/s ²
Sound Pressure	91 dB(A)
Sound Pressure Uncertainty	3 dB(A)
Sound Power	102 dB(A)
Sound Power Uncertainty	3 dB(A)