## D28715-GB

**14-Inch High Performance** Chop Saw 220V

## **FEATURES**



- Keyless blade clamp allows quick, hassle free blade change
- Electronic soft start to limit start-up current and kick back reaction
- High power abrasion protected motor delivers high overload capabilities for greater durability

**GUARANTEED TOUGH:** 

- Keyless mitre adjustments for quick and simple operations
- Cut-off brushes to prevent motor damage at end of brush life
- Horizontal handle for superior ergonomics and less user fatigue
- Large steel base for a large working area and greater stability
- Spindle lock for easy wheel changes
- Keyless vice allows quick material clamping / releasing
- Machined gears for increased durability
- Easy to carry to the jobsite with new integrated carrying handle
- Adjustable spark guard allow the use to adjust the spark direction

## **SPECIFICATIONS**

Power Input	2200 Watts
Power Output	1350 Watt
No Load Speed	4000 rpm
Wheel Diameter	355x2.5 mm
Max. Cutting Capacity at 90° [Square P	rofile] 120x120 mm
Max. Cutting Capacity at 90° [Rectangu	lar Profile] 100x200 mm
Max. Cutting Capacity at 90° [L-Shape I	Profile] 140x140 mm
Max. Cutting Capacity at 90° [Rounded	Profile] 130 mm
Max. Cutting Capacity at 45° [Square P	rofile] 113x113 mm
Max. Cutting Capacity at 45° [Rectangu	lar Profile] 100x140 mm
Max. Cutting Capacity at 45° [L-Shape I	Profile] 120x120 mm
Max. Cutting Capacity at 45° [Rounded	Profile] 130 mm
Weight	18 kg
Length	520 mm
Height	435 mm
Sound Pressure	100 dB(A)
Sound Pressure Uncertainty	3 dB(A)
Sound Power	112 dB(A)
Sound Power Uncertainty	3 dB(A)

Vatt om 5 mm 20 mm )0 mm 10 mm n 3 mm l0 mm 20 mm n n n (A) ) (A) )



## www.aabtools.com