

98

PAINT MIXERS

Paint mixers are ideal for mixing paint and a multitude of other low density materials. Manufactured from a 5/16"(8mm) hexagonal shaft with fluted construction, these have an attractive red powder coated finish for increased protection against rust.

Using Paint Mixers

Place Paint Mixer in the container of material and gently work around the container edges till the material starts flowing towards the center of the blades.

- Continue to gently work on the material till it is of desired consistency.
- For coarse or stiff materials, reverse the direction of the drill and follow above steps. The mixer works best with a variable speed reversible drill machine with 400 – 600 watts minimum power. Recommended speed between 200 – 700 rpm depending upon the material being mixed.

Important

- Do not use Paint Mixer with lacquer or other such inflammable liquids [with flashpoint under 32°C (70°F)]
- Insert mixer well into the material before turning on the drill.
- When mixing is complete, wait for the mixer to come to a halt before removing it from the container.

Cat. Nr.	Ordering Nr.	Dia. of Mixing Wheel		Length		Fits Drill Size	
		Inch	mm	Inch	mm	Inch	mm
♦ PMX/60	14620	2.3/8	60	16	400	3/8	9.5
PMX/80	14621	3.3/16	80	16	400	3/8	9.5

♦ BESTSELLER



99

REVOLVING PUNCH PLIER


Professional quality pliers, these are made from heavy gauge pressed steel sheet and are used to punch holes in leather, canvas, plastics, watch bands, belts etc.

Punches are accurately heat treated for extended life and are exposed to a brass anvil which prevents the edges from getting damaged in use. Each punch locates exactly in position locking in place with the pawl and ratchet mechanism.

Spring loaded revolving head incorporates 6 punches of sizes 5/64" (2 mm), 3/32"(2.5 mm), 1/8"(3.0 mm), 9/64" (3.5 mm), 5/32"(4 mm) & 3/16" (4.5 mm).

Cat. Nr.	Ordering Nr.	Length	
		Inch	mm
♦ RPL/6	31600	8.3/4	220

♦ BESTSELLER



45-55 HRC

CRC steel sheet

