

Indestructible handle is made up of 6 spring steel bars that run all the way through the handle

Bars are locked with the hammer head using steel locking plates ensuring that the head never gets dislodged

Ergonomic rubber grip handle absorbs vibration and reduces fatigue.

Special bonding process ensures that the head never gets loose from the handle

These are available in 2 types:

Heavy Duty 50-58 HRC Head*

Forged from special steel, the hammer head is induction case hardened 50-58 HRC. These hammers are especially useful in demolition work where the struck surface is softer than the hammer head. These are also available with a short handle (12-16" length), especially useful in automotive applications

UTILITY

- Driving in stakes
- Heavy demolition work
- Construction: fracturing stone & concrete
- Driving fence posts
- Police, fire & rescue
- Rebar work
- Railroads
- Bending & shaping metal

WARNING*

Do not strike objects harder than 46 HRC. Striking items of a greater hardness is liable to cause fracture or chipping



Heavy Duty 52 HRC Head

PATENT PENDING

Soft Face 30 HRC Head

Soft Face 30 HRC Head:

Forged from special steel, the hammer head is induction case hardened & then tempered to reduce hardness to within 30-35 HRC. Softer head is designed to mushroom when striking harder base materials. Prevents damage to struck work pieces

UTILITY

- Construction
- Agriculture
- Automotive
- Overground mining
- Railroad
- Maintenance of cutting tools

WORKING TEMPERATURE RANGE

-10°C TO 50°C
(14°F TO 122°F)



Steel Locking Plate



6 Spring Steel Bars



Ergonomic Rubber Grip Handle

BS 876

For material, hardness & performance

SANS 387:2014



ORDERING INFORMATION

CAT NR.	HEAD WEIGHT		OVERALL LENGTH		BOX QTY.
	(LBS)	(KG)	(INCH)	(MM)	
HEAVY DUTY 52 HRC HEAD					
SHID/6/24	6	2.7	24	600	4
SHID/6/30	6	2.7	30	750	4
*SHID/8/24	8	3.6	24	600	4
*SHID/8/30	8	3.6	30	750	4
SHID/10/30	10	4.5	30	750	4
SHID/12/30	12	5.5	30	750	4
*SHID/14/30	14	6.3	30	750	4
◆SHID/20/36	20	9	36	900	4

* Best Seller ◆ New

CAT NR.	HEAD WEIGHT		OVERALL LENGTH		BOX QTY.
	(LBS)	(KG)	(INCH)	(MM)	
SOFT FACE 30 HRC HEAD					
◆SHID/SF/6/30	6	2.7	30	750	4
◆SHID/SF/8/30	8	3.6	30	750	4
◆SHID/SF/10/30	10	4.5	30	750	4
◆SHID/SF/12/30	12	5.5	30	750	4
◆SHID/SF/14/36	14	6.3	36	900	4