

02

Sledge Hammers

SHID

Indestructible handle is made up of 6 spring steel bars that run all the way through the handle.

Bars are locked with the hammer head using steel locking plates ensuring that the head never gets dislodged.

Ergonomic rubber grip handle absorbs vibration and reduces fatigue.

Special bonding process ensures that the head never gets loose from the handle.




Heavy Duty
52 HRC Head

Soft Face
30 HRC Head



Steel Locking Plate



6 Spring Steel Bars



Ergonomic Rubber Grip Handle

These are available in 2 types:

Heavy Duty 50-58 HRC Head*

Forged from special steel, the hammer head is induction case hardened 50-58 HRC. These hammers are especially useful in demolition work where the struck surface is softer than the hammer head. These are also available with a short handle (12-16" length), especially useful in automotive applications

UTILITY

- Driving in stakes
- Heavy demolition work
- Construction: fracturing stone & concrete
- Driving fence posts
- Police, fire & rescue
- Rebar work
- Railroads
- Bending & shaping metal

Soft Face 30 HRC Head:

Forged from special steel, the hammer head is induction case hardened & then tempered to reduce hardness to within 30-35 HRC. Softer head is designed to mushroom when striking harder base materials. Prevents damage to struck work pieces.

UTILITY

- Construction
- Agriculture
- Automotive
- Overground mining
- Railroad
- Maintenance of cutting tools

BS 876

For material, hardness & performance

SANS 387:2014



ORDERING INFORMATION

CAT NR.	ORD NR.	HEAD WEIGHT		HANDLE LENGTH	
		lbs	kg	inch	mm
HEAVY DUTY 52 HRC HEAD					
SHID/6/16	34521	6	2.7	16	400
SHID/6/24	34510	6	2.7	24	600
SHID/6/30	34511	6	2.7	30	750
SHID/8/12	34522	8	3.6	12	300
SHID/8/16	34523	8	3.6	16	400
SHID/8/24	34512	8	3.6	24	600
SHID/8/30	34513	8	3.6	30	750
SHID/8/36	34517	8	3.6	36	900
SHID/10/30	34514	10	4.5	30	750
SHID/10/36	34518	10	4.5	36	900
SHID/12/30	34515	12	5.5	30	750
SHID/12/36	34519	12	5.5	36	900
SHID/14/30	34516	14	6.3	30	750
SHID/14/36	34520	14	6.3	36	900

WARNING*

Do not strike objects harder than 46 HRC. Striking items of a greater hardness is liable to cause fracture or chipping

WORKING TEMPERATURE RANGE

-10°C TO 50°C
(14°F TO 122°F)

CAT NR.	ORD NR.	HEAD WEIGHT		HANDLE LENGTH	
		lbs	kg	inch	mm
SOFT FACE 30 HRC HEAD					
SHID/SF/6/30	34560	6	2.7	30	750
SHID/SF/8/30	34561	8	3.6	30	750
SHID/SF/10/30	34562	10	4.5	30	750
SHID/SF/12/30	34563	12	5.5	30	750
SHID/SF/14/36	34565	14	6.3	36	900