

04

Copper Head Sledge Hammers

CHID-CU

SHID-CU

Indestructible handle is made with spring steel bars that run all the way through the handle.

Bars are locked with the hammer head using steel locking plates ensuring that the head never gets dislodged.

Ergonomic rubber grip handle absorbs shock & vibration reducing fatigue.

Special bonding process ensures that head never gets loose from the handle.


Hammer head is forged from 99.9% pure copper for spark free use. Copper head resists sparking & reduces marring of most struck surfaces

UTILITY

- Metal forming
- Mining
- Underground coal mining



Spark Resistant!






Steel Locking Plate



4 - 6 Spring Steel Bars



Ergonomic Rubber Grip Handle

MATERIAL	HARDNESS	NON SPARKING	NON MARRING
Cu COPPER	 85 HV		

ORDERING INFORMATION

CAT NR.	ORD NR.	HEAD WEIGHT		HANDLE LENGTH	
		lbs	kg	inch	mm
CHID/2.5/12/CU	34602	2.5	1.1	12	300
CHID/2.5/16/CU	34603	2.5	1.1	16	400
CHID/4/12/CU	34600	4	1.8	12	300
CHID/4/16/CU	34604	4	1.8	16	400
SHID/8/24/CU	34610	8	3.6	24	600
SHID/14/30/CU	34611	14	6.3	30	750

WORKING TEMPERATURE RANGE

-10°C TO 50°C
(14°F TO 122°F)