Husqvarna VARI-CUT W1120

With their unique design, Husqvarna's wall saw bladesensure top performance in terms of product life and cuttingproperties. In production the latest technologies as well ashigh-quality components are used, to maximise productreliability and consistency. The W 1100 series consists of blades with a high cuttingspeed and a good balance between cost and performance.

Sandwich segment design

Helps the blade to retain the shape ensuring superior cutting speed and maximum utilisation of the full segment height.

Good balance between performance and cost

This diamond tool has a good performance/price ratio thanks to the high performance output in relation to the tool investment.

High cutting capacity

Longitudinal 60x60 tiles and slabs and diagonal cutting of 40x40 tiles and slabs.

Efficient cooling

The notch design of the segments provides efficient cooling of the blade, and evacuates the abrasive slurry.

FEATURES

- High cutting capacity
- This diamond tool has a good performance/price ratio thanks to the high performance output in relation to the tool investment.
- Helps the blade to retain the shape ensuring superior cutting speed and maximum utilisation of the full segment height.
- The notch design of the segments provides efficient cooling of the blade, and evacuates the abrasive slurry.

Technical Specifications	
GENERAL	
Article Description	1000W 4.5 60.0 W1120
Performance grade	Silver
Blade configuration	Segmented
Coolant	Wet
Power range, max kW	19 kW
Power range, min kW	15 kW
DIMENSIONS	
Diameter mm	1000 mm
Arbor diameter	60 mm
Segment height mm	14 mm
Segment length mm	40 mm
Segment width mm	4.5 mm
Article gross weight	23918 g
Article net weight	21500 g
MATERIALS	
Brick	Good
Concrete hard	Acceptable
Concrete medium	Good
Concrete soft	Optimal
Highly reinforced concrete	Acceptable
Reinforced concrete	Good
PACKAGING	
Packaging length	1030 mm
Packaging width	1030 mm
Packaging height	25 mm