

## SP 2 Flat

Copes with up to 6,000 l/h and pumps out water down to 1 mm, leaving the surface mop dry: The SP 2 Flat submersible flat suction pump is the compact entry-level pump for clear to lightly contaminated water.

















- 1 Ceramic face seal.
- For an extra long lifetime.

## 2 Float switch

Switches the pump on and off again according to the water level, preventing dry running.

## 3 Quick Connect

Connection thread for quick and uncomplicated connection of 1 1/4" hoses to the pump.

#### 4 Foldable legs

Switching from normal operation with a higher capacity to 1 mm flat pick-up with a mop dry result.

# **TECHNICAL DATA AND EQUIPMENT**





## SP 2 Flat

Technical data		
EUI order number		1.645-501.0
EAN code		4054278059402
Max. motor rating	W	250
Max. flow rate	l/h	< 6000
Delivery temperature, max.	°C	35
Delivery height / Max. pressure	m / bar	5 / 0.5
Flat pick-up to a depth of	mm	1
Max. grain size	mm	5
Max. immersion depth	m	7
Min. residual water, manual	mm	1
Suction up to	mm	1
Connection thread		G1
		G1 internal thread
Power cable	m	H05RN-F / 10
Weight without accessories	kg	3.8
Dimensions (L × W × H)	mm	227 × 240 × 262
Equipment		
Comfortable carrying handle		
Hose connection piece		1 1/4"

Equipinent	
Comfortable carrying handle	
Hose connection piece	1 1/4"
Easy hose connection thanks to Quick Connect	•
Switching between manual/automatic operation	Possibility of fixing the float switch
Switch to flat pick-up	
Float switch	
Ceramic face seal.	1
■ Included in the scope of supply	

# SP 2 FLAT 1.645-501.0











		Order no.				Price	Description
Suction hoses							
Suction hose available in bulk	2	6.997-347.0 6.997-346.0					Vacuum-resistant spiral hose can be cut to length for connection to submersible, garden, submersible pressure pumps and high-pressure pumps.
Miscellaneous							
Flat hose set	3	2.997-100.0					Space-saving hose set with a flexible fabric hose, including stainless steel hose clamp for connecting to submersible pumps. Ideal as a feed hose for water removal in the event of flooding.
Adapters / connectors				'	,		
Pump adapter including check valve, small	4	6.997-359.0					Pump adapter with check valve for vacuum-resistant connection of suction hoses to pumps (e.g. garden pumps and high-pressure pumps for domestic use).
Filter		1	1	1			The state of the s
Prefilter for submersible pumps, small	5	2.997-201.0					Protects the submersible pump and thereby improves its operational reliability: the robust and easy-to-fit prefilter for the SP 1 to SP 5 Flat/Dirt submersible pumps.

<sup>☐</sup> Available accessories.

# SP 2 FLAT 1.645-501.0









		Order no.			Price	Description	
Hoses				'			
PrimoFlex® Plus hose 3/4" - 25 m	1	2.645-148.0					
PrimoFlex* hose 3/4" - 25 m	2	2.645-142.0				PrimoFlex* quality garden hose (3/4"). 25 m long. With pressure-resistant woven reinforcement. Contains no substances that are harmful to health. Bursting pressure: 24 bar. High temperature resistance from -20 to 65 °C.	
PrimoFlex* hose 1" 1 m	3	2.645-247.0				-	

☐ Available accessories.