



— PRODUCT DATA SHEET

P7



P7

SPECIFICATIONS

TECHNICAL DATA

Length defocused [mm]	130
Length focused [mm]	140
Head diameter [mm]	37
Tube diameter [mm]	30
Weight incl. batteries [g]	175
Weight without batteries [g]	130
Focus function	Yes
Head material	Aluminum alloy
Tube material	Aluminum alloy
Optic	Plastic lense (PMMA)
Cartridge	Yes

POWER SUPPLY

Power source type	Battery
Battery quantity	4
Battery type	Alkaline
Battery description	Micro (AAA) 1.5V
Rechargeable	No
Energy modes	Energy Saving
Usable batteries	AAA NiMH 1.2V

FURTHER SPECIFICATIONS

IP class	IPX4
Drop test (drop height) [m]	1
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS

Low Power, Mid Power, Power

LIGHT SOURCE

Amount LEDs	1
LED type	High Power LED
Color	White
Color temperature [K]	6000 to 8000
Color rendering index (CRI)	70

LIGHT VALUES

	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]		450	250	40
Beam distance ¹ [m]		300	220	100
Run time ¹ [h]		1	2	25

SWITCH

End Cap Switch

TECHNOLOGIES

Advanced Focus System³, Rapid Focus

7
YEAR
WARRANTY⁴

PACKAGING AND LOGISTICS



Exemplary Packaging Illustration



Exemplary Packaging Illustration

PACKAGING INFORMATION

Type of packaging	Test It Blister
Scope of delivery	2 sets of batteries, Hand strap, Pouch
Item No.	500900
Customs tariff number	85131000

PACKAGING INFORMATION

Type of packaging	Gift Box
Scope of delivery	1 set of batteries, Hand strap, Pouch
Item No.	501046
Customs tariff number	85131000

ACCESORIES

PRODUCT CATEGORY	ITEM NUMBER	PRODUCT NAME
Pouches / Holster	0039	Pouch with Color Filter Set
Color filter / Signal caps	0040-W	Signal Cone W 37mm
Color filter / Signal caps	0040	Signal Cone 37mm
Roll Protections	0313	Roll Protection 37mm
Color filter / Signal caps	100879	Color Filter Set 37mm
Fastenings / Brackets	501034	GoPro Adapter Set Type A
Fastenings / Brackets	0317	Intelligent Clip Type C
Roll Protections	0320	Roll Protection Ring 29,5 mm
Pouches / Holster	0333	Pouch Type A
Remote Switches	0361	Remote Switch Type B
Fastenings / Brackets	0362	Universal Mounting System
Fastenings / Brackets	7799-PT	Universal Mounting Bracket Type B
Roll Protections	0313-F	Color Filter Set + 1x Rollprotection 37mm

P7

MARKETING

KEY SELLING POINTS

- Excellent Ledlenser lighting quality – Brightness, beam distance and lighting duration are ideally coordinated for the energy source
- From the homogeneous circle of close range lighting (defocused) to a sharply bundled long –distance beam (focused) – The patented³ Advanced Focus System with reflector lense enables efficient, tailored lighting
- Wide range of applications – Comprehensive accessories
- Sustainability thanks to modular construction – For example, easily exchanged battery cartridge
- For a long lifetime – Robust metal housing and high-quality gold contacts

PRODUCT COPY

The Ledlenser P7

A Ledlenser exactly how you want it.

We appreciate your feedback. With the P7 we've put many of your suggestions regarding the previous model into practice. A larger profiled switch makes it easier to use when wearing gloves. The lens has been redesigned and equipped with the latest LED technology. And even ergonomically speaking we have made changes based on your wants. This makes the light an allrounder with indestructible technology and extreme durability.

SERIES COPY

The Ledlenser P-Series

Minimalist design, maximum performance.

The sturdy flashlights of the Ledlenser P-Series offer top performance in stylish designs. While externally they only have the bare essentials, they are packed full of useful technical functions, like the Rapid Focus and the Advanced Focus System. This makes them to indispensable little helpers for everyday life: For example, for renovating, tidying and rearranging, taking the dog out, during blackouts, and much more.

FOOTNOTES

The information pertaining to package contents, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change package contents, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurements according to ANSI FL1 on the respective setting. Average values, in some cases, deviations by +/- 15 % may occur due to technical reasons. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting and to battery duration (hours/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light has different energy modes, measurement is based on "energy saving mode."

3) EP Patent 1880139, US Patent 7,461,960

4) Warranty period of five years from the date of purchase, seven years if the product is registered online on our website. The warranty is valid worldwide and legal warranty rights also apply. It covers defects in materials and workmanship. For the proper functioning of rechargeable batteries a different warranty period of 24 months applies. Excluded from this warranty are the products of the "Solidline" series, Ledlenser K1 and Ledlenser K2. The warranty does not apply to Defects in batteries, holsters, pouches, remote switches, color filters, imprints or surface coatings. The guarantor is Zweibrüder Optoelectronics GmbH & Co. KG, Kronenstr. 5 - 7, 42699 Solingen, Germany. More information: ledlenser.com/warranty"

