ELECTRICAL

Bolt Cutters



Bolt Cutters

- Hardened alloy steel jaws are designed and manufactured to assure the longest possible blade life.
- One-step internal cam mechanism provides the quickest and simplest way to keep the cutting blades precisely aligned.
- Handles and grips designed to allow greater mechanical advantage for crisp, controlled

| | | Description | Capacity/Metals | | | | | | Weight | |
|----------------|--------------|-------------|--------------------------|------|----------------------------|------|--------------------------|------|--------------------------------|------|
| Catalog No. | Model No. | | Soft (15RC) ¹ | | Medium (31RC) ² | | Hard (42RC) ³ | | | |
| | | | in. | mm | in. | mm | in | mm | lb. | kg |
| 14213 | S14 | Center Cut | 5/16 | 7.9 | 1/4 | 6.4 | 3/16 | 4.8 | 1 ¹ / ₄ | 1.00 |
| 14218 | S18 | Center Cut | 3/8 | 9.5 | 5/16 | 7.9 | 1/4 | 6.4 | 33/8 | 1.50 |
| 14223 | S24 | Center Cut | 7/16 | 11.0 | 3/8 | 9.5 | 5/16 | 7.9 | 5 ⁷ /8 | 2.70 |
| 14228 | S30 | Center Cut | 1/2 | 12.7 | 7/16 | 11.0 | 3/8 | 9.5 | 87/8 | 4.00 |
| 14233 | S36 | Center Cut | 9/16 | 14.3 | 1/2 | 12.7 | 7∕16 | 11.0 | 131/2 | 6.10 |
| 14238 | S42 | Center Cut | 11/16 | 17.5 | 9/16 | 14.3 | 1/2 | 12.7 | 18 ¹ / ₄ | 8.30 |

Replacement Heads

| Catalog No. | Description | Weight | | |
|----------------|-------------------|--------------------------------|-----|--|
| | Description | lb. | kg | |
| 18363 | S14 Head Assembly | 7/8 | 1.0 | |
| 18368 | S18 Head Assembly | 11/4 | 1.5 | |
| 18373 | S24 Head Assembly | 21/4 | 2.7 | |
| 18378 | S30 Head Assembly | 87/8 | 4.0 | |
| 18383 | S36 Head Assembly | 13 ¹ / ₂ | 6.1 | |
| 18388 | S42 Head Assembly | 18 ¹ / ₄ | 8.3 | |

Cable Cutters



No. 1380 Cable Cutter

• The Model 1380 Cable Cutter is designed to shear-cut insulated aluminum and copper cable through 13/8" diameter and 750 MCM*. Drop-forged, heat-treated, alloy steel jaws shear cable with minimum distortion of internal wires. Fitted with fiberglass-insulated handles and rubber grips.

*Not intended for cutting steel or ACSR cable.

| | Catalog No. Description | | Description | | Weight | |
|--|-------------------------|------|---|------|--------|--|
| | | | Description | lb. | kg | |
| | 83350 | 1380 | Aluminum and Copper Cable through 13/8 Diameter and 750 MCM | 41/2 | 2.0 | |