

EXTREME[®] DEWALT[®] BONDED ABRASIVES OSA[®]

Disc diameter
Date of expiry
Application
Max. speed (rpm)*
OSA no.
Safety symbols
Disc thickness
Bore diameter
Cat. No.
Disc material
European standard
OSA-Logo
EAN

MAX RPM
5,600min⁻¹rpm
MAX 60m/s

A24R7BF
EN12413

OSA

DX7987-AE



Ø230x3.0x22.2mm

Type 1 Flat Discs
Type 42 Depressed Discs

METAL CUTTING DISCS



Ø100-230 mm



APPLICATIONS

- Cutting ferrous metals such as steel, iron, rebar and welds

FEATURES

- Professional grade aluminium oxide
- Premium resin bond
- Reinforced fibre glass

FOR USE WITH

Angle grinders.





DEPRESSED CENTRE

Cat. No.	Diameter mm	Bore mm	Thickness mm	Grit/Bond	Pack Qty.
DX7907-AE	100	16.0	3.0	A24R7BF	25
DX7927-AE	115	22.2	3.0	A24R7BF	25
DX7947-AE	125	22.2	3.0	A24R7BF	25
DX7967-AE	180	22.2	3.0	A24R7BF	25
DX7987-AE	230	22.2	3.0	A24R7BF	25

METAL GRINDING DISCS



Ø100-230 mm



APPLICATIONS

- For general metal grinding applications on ferrous and non-ferrous metals, including weld and surface preparation

FEATURES

- Professional grade aluminium oxide
- Reinforced fibre glass

FOR USE WITH

Angle grinders.




DEPRESSED CENTRE

Cat. No.	Diameter mm	Bore mm	Thickness mm	Grit/Bond	Pack Qty.
DX7901-AE	100	16.0	6.0	A30R7BF	10
DX7921-AE	115	22.2	6.0	A30R7BF	10
DX7941-AE	125	22.2	6.0	A30R7BF	10
DX7961-AE	180	22.2	6.0	A30R7BF	10
DX7981-AE	230	22.2	6.0	A30R7BF	10

STAINLESS STEEL CUTTING AND THIN CUTTING DISCS



Ø100-230 mm



APPLICATIONS

- Fast cutting and long life in harder metals

FEATURES

- Professional grade aluminium oxide
- Reinforced fibre glass
- Premium resin bond


FOR USE WITH

Angle grinders and cut-off saws.



FLAT

Cat. No.	Diameter mm	Bore mm	Thickness mm	Grit/Bond	Pack Qty.
DT3440-QZ	100	16.0	1.0	A60 TBF	25
DT3442-QZ	115	22.2	1.0	A60 TBF	25
DT3445-QZ	125	22.2	1.0	A60 TBF	25
DX8055	230	22.2	1.9	AS46INOXBF	25




DEPRESSED CENTRE

Cat. No.	Diameter mm	Bore mm	Thickness mm	Grit/Bond	Pack Qty.
DX7907S-AE	100	16.0	3.0	AS24R7BF Inox	25
DX7927S-AE	115	22.2	3.0	AS24R7BF Inox	25
DX7947S-AE	125	22.2	3.0	AS24R7BF Inox	25
DX7967S-AE	180	22.2	3.0	AS24R7BF Inox	25
DX7987S-AE	230	22.2	3.0	AS24R7BF Inox	25

STAINLESS STEEL GRINDING DISCS



Ø100-230 mm



APPLICATIONS

- Fast cutting and long life in harder metals

FEATURES

- Professional grade aluminium oxide and silicone carbide

FOR USE WITH

Angle grinders.



DEPRESSED CENTRE

Cat. No.	Diameter mm	Bore mm	Thickness mm	Grit/Bond	Pack Qty.
DX7901S-AE	100	16.0	6.0	AS30R7BF Inox	10
DX7921S-AE	115	22.2	6.0	AS30R7BF Inox	10
DX7961S-AE	180	22.2	6.0	AS30R7BF Inox	10
DX7981S-AE	230	22.2	6.0	AS30R7BF Inox	10